

Tollmark Address Lights

(800) 477-7723

www.tollmarkaddresslights.com

Use Only Replacement Bulbs & Parts Provided by Tollmark

All Others Will Void Warranty

ADDRESS LIGHT SPECIFICATIONS

(4 & 6 Inch Illuminated Identification Number Signs)

HOUSING FRONT: Powder-coated Paint-Loc Steel

MOUNTING PLATE: Aluminum with white gloss powder-coating

HOUSING DIMENSIONS: (Note: All housing heights are greater than the number heights)

4 Inch Numbers

Standard Housing

Stepped Housing

(Large) Holds 1 to 7 digit addresses

(L) 14.5" x (H) 5.5" x (D) 2.0"

(L) 15.75" x (H) 6.75" x (D) 2.0"

(Small) Holds 1 to 5 digit addresses

(L) 9.5" x (H) 5.5" x (D) 2.0"

(L) 10.75" x (H) 6.75" x (D) 2.0"

6 Inch Numbers

Standard Housing

Holds 1 to 6 digit addresses

(L) 14.5" x (H) 7.5" x (D) 2.0"

NUMBERS: HEIGHT 4.0" or 6.0" (horizontal orientation).

NUMBER PANEL: White translucent acrylic sheet with high contrast commercial grade high performance exterior signage vinyl laminate.

LIGHTING: Small Size Standard or Stepped Housings - Takes (2) #655 Wedge Base Bulbs.

6 Inch Numbered & Large Size Standard or Stepped Housings - Takes (4) #193 Wedge Base Bulbs.

POWER SOURCE: Listed 12 - 16 vac (8 Watt minimum capacity) Class II Transformer. USE OF UNLISTED AND / OR TRANSFORMER OVER 16 VAC VOIDS WARRANTY.

WIRING: Listed 2 conductor insulated copper wire #18 awg - #22 awg. USE OF SMALLER GAUGE WIRE VOIDS WARRANTY. Runs over 50 feet are not recommended.

ELECTRICAL

SPECIFICATIONS: #655 BULB UNITS (2 bulbs/ unit)

#193 BULB UNITS (4 bulbs/ unit)

VOLTAGE SUPPLIED

12 VOLTS 16 VOLTS

VOLTAGE SUPPLIED

12 VOLTS 16 VOLTS

AMPs

0.20

0.22

0.40

0.48

WATTS

2.40

3.52

4.80

7.68

MOUNTING: Surface mounts on most surfaces - Mount so end screws that join housing front and backplate remain accessible so future maintenance can be performed.

INSTALLATION: This service is not provided by Tollmark Address Lights.